



AN AMERICAN WORKHORSE SINCE 1916

TURN TO THE ONE MACHINE THAT'S ALL BUSINESS.
EVERYTHING HERE HAS BEEN RATCHETED UP,
EVERYTHING THAT IS, EXCEPT THE PRICE.



Accessories/ Attachments

Optional:

- 3 BUCKET X-TREME FLO™
BAGGER KIT
- BAR STYLE TIRE KIT
- DISCHARGE COVER KIT
- FLEXTEND™ SHOULDER
SUPPORT SYSTEM
- GRAVELLY SEAT COVER
- HEADLIGHT KIT
- MULCHING KIT
- OPERATOR CONTROLLED
DISCHARGE CHUTE
- SOLID FRONT CASTER
TIRE KIT
- STRIPING KIT
- TRAILER HITCH KIT
- VACUUM BAFFLE KIT
- CHROME WHEEL COVER

PROFESSIONAL

Pro-Turn™ 200 XDZ Series

- **Adjustable foot pedal** makes raising the deck easier for all sizes of individuals
- **7-gauge fabricated and welded X-Factor® Deck Design** assures lasting performance
- **Maintenance-free XL Spindles®** with durable cast iron housings
- **1/2" wear bar** integrated into the deck and two additional gussets guard against leading edge or baffle bending
- **Heavy-duty rubber discharge chute** provides flexibility for mowing around objects
- **Wider stance** improves overall stability and traction on uneven terrain providing more operator confidence
- **Double-sided anti-scalp brackets** eliminate bending and breaking of scalp rollers
- **Full-suspension seat** cradles the operator in comfort; has been lowered to increase overall mower stability
- **Unique boxed frame** for engine and transmission adds strength and support; while four isolation points reduce operator cockpit vibration by 45% compared to the competition
- **Foldable ROPS is standard** providing extra protection to the operator
- **Large diameter steering arms** and vibration isolators add comfort and control while reducing operator fatigue
- **Designated trailer tie-down points** safeguard the machine during transport
- **Simplified, yet beefed-up deck lift** with 17 cutting positions in 1/4" increments incorporates easy-to-use deck leveling system and eliminates over-hung loads
- **Heavy-duty hanger chains** add strength



PRO-TURN™ 200 XDZ SERIES

PRODUCT NAME	Pro-Turn 252	Pro-Turn 252	Pro-Turn 260	Pro-Turn 260	Pro-Turn 260	Pro-Turn 266
MODEL NUMBER	992200	992205	992201	992204	992203	992202
ENGINE	Kawasaki® FX730V	Kohler® EFI	Kawasaki® FX751V	Kohler® EFI	Kawasaki® FX850V	Kawasaki® FX850V
	Air-cooled Vertical twin	Air-cooled Vertical twin	Air-cooled Vertical twin	Air-cooled Vertical twin	Air-cooled Vertical twin	Air-cooled Vertical twin
	Heavy-Duty Air Cleaner	Heavy-Duty Air Cleaner	Heavy-Duty Air Cleaner	Heavy-Duty Air Cleaner	Heavy-Duty Air Cleaner	Heavy-Duty Air Cleaner
HORSEPOWER	23.5	29	24.5	29	27	27
DISPLACEMENT (cc)	726	747	852	747	852	852
DRIVE SYSTEM	Hydro-Gear® ZT-5400 Integrated pump/motor					
FUEL CAPACITY - Gallons (LITERS)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph
STARTER	Electric	Electric	Electric	Electric	Electric	Electric
DECK						
DECK MATERIAL	7 GA Steel with .25 inch Spindle Reinforcement					
DECK CONSTRUCTION	Welded	Welded	Welded	Welded	Welded	Welded
NUMBER OF SPINDLES	3	3	3	3	3	3
BLADE TIP SPEED (FPM)	18,000	18,000	18,000	18,000	18,000	18,000
SPINDLE HOUSING MATERIAL	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
SPINDLE SHAFT	Steel	Steel	Steel	Steel	Steel	Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Ogura® GT3.5 Electric Clutch	Ogura® GT3.5 Electric Clutch	Ogura® GT3.5 Electric Clutch	Ogura® GT3.5 Electric Clutch	Ogura® GT3.5 Electric Clutch	Ogura® GT3.5 Electric Clutch
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated
CUTTING WIDTH	52"	52"	60"	60"	60"	66"
CUTTING HEIGHTS	1.5"-5.5"	1.5"-5.5"	1.5"-5.5"	1.5"-5.5"	1.5"-5.5"	1.5"-5.5"
CUTTING POSITIONS	17	17	17	17	17	17
TIRES						
FRONT AXLE	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
FRONT	Smooth 15 x 6-6	Smooth 15 x 6-6	Smooth 15 x 6-6	Smooth 15 x 6-6	Smooth 15 x 6-6	Smooth 15 x 6-6
REAR	Turf 23 x 10.5-12	Turf 23 x 10.5-12	Turf 24 x 11.5-12	Turf 24 x 11.5-12	Turf 24 x 11.5-12	Turf 24 x 11.5-12
FEATURES						
HOOD	N/A	N/A	N/A	N/A	N/A	N/A
SEAT	High-Back w/ Full Suspension	High-Back w/ Full Suspension	High-Back w/ Full Suspension	High-Back w/ Full Suspension	High-Back w/ Full Suspension	High-Back w/ Full Suspension
HOOR METER	Standard	Standard	Standard	Standard	Standard	Standard
SUSPENSION SEAT	Standard	Standard	Standard	Standard	Standard	Standard
FOLDABLE ROPS	Standard	Standard	Standard	Standard	Standard	Standard
MACHINE DIMENSION						
WEIGHT (lbs)	1189	1189	1254	1254	1254	1284
LENGTH (inches)	80	80	80	80	80	80
WIDTH (inches)	55.5 (w/o chute)	55.5 (w/o chute)	63 w/o chute	63 w/o chute	63 w/o chute	67.5 w/o chute
HEIGHT W/ ROPS EXT/DOWN (inches)	70/47.75	70/47.75	70/47.75	70/47.75	70/47.75	70/47.75
WARRANTY						
UNIT	2 Year Limited Commercial					
DECK SHELL & FRAME	Limited Lifetime Deck Shell & Frame					
SPINDLES	3 Year Limited Spindle					

Updated 2/2012

An *Ariens* Company Brand

© Copyright 2012 Ariens Company. ® Registered trademark and ™ trademark of Ariens Company, Briggs & Stratton, Generac, Hydro-Gear, Kawasaki, Kohler, Ogura, Parker, Subaru and Warner are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit www.ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of product; product may differ.



WWW.GRAVELY.COM