

PRO-TURN® 100 SERIES

LEARN MORE AT [GRAVELY.COM](https://www.gravelly.com)

Uncompromised Gravelly performance with a slightly smaller price tag. We've taken 100 years of experience and turned the Pro-Turn 100 into the toughest, most versatile and powerful commercial value on the market.



X-FACTOR® II DECK The 7-gauge, all-steel welded X-Factor® II Deck is fabricated from top to bottom, providing industrial strength peace of mind that's reinforced with an exclusive limited lifetime warranty.

CBT SYSTEM our exclusive Constant Belt Tension System (CBT) ensures that belt tension is constant, keeping the blade tip speed and cutting results consistent.

ROPS foldable ROPS comes standard to provide additional protection for the operator.

INSIGHTFUL DESIGN an updated design creates improved operator experience, providing a clear line of sight to the deck cutting edge.

SEATING SYSTEM the high-back suspension seats provides improved lateral stability with added vibration control and a 4-inch seat slide for all-day comfort.



NO HOUR LIMIT FIRST TWO YEARS

LIMITED LIFETIME DECK SHELL & FRAME

See your professional Gravelly® dealer for complete warranty details.



PRODUCT NAME	PRO-TURN 148	PRO-TURN 152	PRO-TURN 160	PRO-TURN 152	PRO-TURN 160	PRO-TURN 160	PRO-TURN 160
MODEL #	991128 / 991137*	991129 / 991138*	991130 / 991139*	991132 / 991135	991133	991136	991140
ENGINE	Kawasaki® FX691V	Kawasaki® FX691V	Kawasaki® FX730V	Kohler® ZT730 / Kohler® EZT725 EFI	Kohler® ZT740	Kohler® EZT740 EFI	Yamaha® MX800V
	Air-Cooled Vertical Twin						
	Heavy-Duty Air Cleaner						
HORSEPOWER	22 hp	22 hp	23.5 hp	23 hp / 22 hp	25 hp	25 hp	26 hp
DISPLACEMENT	726 cc	726 cc	726 cc	747 cc / 725 cc	747 cc	747 cc	824 cc
DRIVE SYSTEM	Hydro-Gear® ZT-3400						
FUEL CAPACITY	10 Gallon (37.8 L)						
GROUND SPEED (APPROX. MPH) (FWD/REV)	10 mph / 5 mph						
STARTER	Electric						
DECK MATERIAL	7 ga. Steel w/ .25 in Spindle Reinforcement						
DECK CONSTRUCTION	Fabricated						
NUMBER OF SPINDLES	3						
BLADE TIP SPEED (FPM)	18,000						
SPINDLE MATERIAL	Forged Aluminum						
SPINDLE BEARINGS	Ball Bearing						
DECK ENGAGEMENT	Electric Clutch Ogura® GT.75						
DECK LIFT SYSTEM	Foot Operated						
CUTTING WIDTH	48 in	52 in	60 in	52 in	60 in	60 in	60 in
CUTTING HEIGHTS	1.5 in - 5.5 in						
CUTTING POSITIONS	17						
WHEELS FRONT AXLE	Fixed. Greaseable Caster Fork Tubes						
WHEELS (FRONT)	Smooth 13 x 6.50 in - 6 in Pneumatic w/ Greaseable Tapered Roller Bearings						
WHEELS (BACK)	Turf 23 x 10.5 in - 12 in						
SEAT	High Back Comfort w/ Full Suspension						
HOURLY METER	Standard						
ROPS	Foldable						
WEIGHT	1062 lbs / 1051 lbs*	1079 lbs / 1068 lbs*	1121 lbs / 1110 lbs*	1068 lbs / 1073 lbs	1110 lbs	1115 lbs	1136 lbs
LENGTH	78.5 in						
WIDTH W/ CHUTE	62 in	67.5 in	75 in	67.5 in	75 in	75 in	75 in
HEIGHT W/ ROPS	71 in						
HEIGHT W/ ROPS FOLDED DOWN	48 in						
WIDTH W/O CHUTE	50 in	55.5 in	63 in	55.5 in	63 in	63 in	63 in
WARRANTY (UNIT)	5 Year / 1000 Hour Limited Commercial / No Hour Limit First Two Years						
WARRANTY (DECK SHELL & FRAME)	Limited Lifetime Deck Shell & Frame						
ATTACHMENTS & ACCESSORIES	MULCHING KIT, DISCHARGE COVER KIT, HUB CAP KIT, SOLID TIRE KIT, TRUE POWER TIRE KIT, TRAILER HITCH KIT, HEADLIGHT KIT, STRIPING KIT, SUNSHADE KIT, 2 BUCKET POWERED BAGGER KIT (8 BU.)						

GRAVELY.COM

An *Ariens* Company Brand

© Copyright 2018 Ariens Company All rights reserved. Registered trademark and ™ trademark of Ariens Company, Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravelly.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

