

# PRO TURN OF THE CENTURY.

Get face-to-face with the new face of Gravelly Pro-Turns. We know you're going to love it, because you inspired, engineered and built this beast.

This refreshed, industrial strength machine features smarter components, a smoother ride and more intuitive controls. And it's all thanks to you.

So give yourself a pat on the back and then get back to work with the next generation of Gravelly Pro-Turns.

*\*Available Only at Professional Dealers*



PRO-TURN 400 SERIES | COMMERCIAL

GRAVELLY.com



## PRO-TURN 400

### LOVE IT FOR LIFE.

#### X-Factor® II Deck

The 7-gauge, all-steel welded X-Factor® II Deck is fabricated from top to bottom, providing industrial-strength peace of mind that's reinforced with an exclusive limited lifetime warranty.

### SUSPENSION OF DISBELIEF.

#### Air-Ride Suspension Seat

Extensive research shows that increased comfort equals increased productivity. Imagine that. So we enhanced the industry's first air-ride suspension with seat isolators to absorb large vertical impacts and an oversized, pillow-top, extra high-back seat for all-day cruising comfort.

### WE'RE TIGHTENING OUR BELTS.

#### All-New CBT System

You're too busy to worry about belts. So we designed our exclusive Constant Belt Tension System (CBT) so that belt tension is constant, your blade tip speed is consistent and your cut results are right on the money.

### ON ANOTHER LEVEL.

#### EZ Lift™ Deck System

This system is decked out. Now raising and lowering the deck requires 25% less effort. Plus, 19 cutting positions with ¼ increments helps eliminate overhung loads.

### IT'S WHAT'S INSIDE THAT COUNTS.

#### Steel Chassis

A heavy duty 1.5" x 3" steel, singular tubular frame is ready for a lifetime of work. Plus, it's fabricated with four engine frame isolation points to reduce cockpit vibration by 45% and lessen operator fatigue.

### IT'S HOW WE ROLL.

#### Radial Rear Tires

Radial rear tires are standard on the Pro-Turn 400, delivering automotive-style performance, industry leading handling and hill holding, while being kinder and gentler to the turf.

PRODUCT NAME	Pro-Turn 452	Pro-Turn 452	Pro-Turn 460	Pro-Turn 460	Pro-Turn 460	Pro-Turn 472	Pro-Turn 472
MODEL NUMBER	992273	992277	992274	992275	992278	992276	992279
ENGINE	Kawasaki® FX850V Air-Cooled w/ Heavy-Duty Air Cleaner	Kohler® ECV 860 EFI Air-Cooled w/ Heavy-Duty Air Cleaner	Kawasaki® FX921V Air-Cooled w/ Heavy-Duty Air Cleaner	Kawasaki® FX1000V Air-Cooled w/ Heavy-Duty Air Cleaner	Kohler® ECV 880 EFI Air-Cooled w/ Heavy-Duty Air Cleaner	Kawasaki® FX1000V Air-Cooled w/ Heavy-Duty Air Cleaner	Kohler® ECV 880 EFI Air-Cooled w/ Heavy-Duty Air Cleaner
HORSEPOWER	27	29	31	35	33	35	33
DISPLACEMENT (CC)	852	824	999	999	824	999	824
DRIVE SYSTEM	Hydro-Gear® ZT-5400 Integrated Pump/Motor	Hydro-Gear® ZT-5400 Integrated Pump/Motor	Hydro-Gear® ZT-5400 Integrated Pump/Motor	Hydro-Gear® ZT-5400 Integrated Pump/Motor	Hydro-Gear® ZT-5400 Integrated Pump/Motor	Hydro-Gear® ZT-5400 Integrated Pump/Motor	Hydro-Gear® ZT-5400 Integrated Pump/Motor
FUEL CAPACITY - GALLONS (LITERS)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)	13.4 (50.7)
GROUND SPEED (APPROX. MPH FORWARD/REVERSE)	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph

### DECK

DECK MATERIAL	7 ga steel with .25" spindle reinforcement	7 ga steel with .25" spindle reinforcement	7 ga steel with .25" spindle reinforcement	7 ga steel with .25" spindle reinforcement	7 ga steel with .25" spindle reinforcement	7 ga steel with .25" spindle reinforcement	7 ga steel with .25" spindle reinforcement
DECK CONSTRUCTION	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated
NUMBER OF SPINDLES	3	3	3	3	3	3	3
BLADE TIP SPEED (FPM)	18,300	18,300	18,600	18,600	18,600	18,200	18,200
SPINDLE HOUSING MATERIAL	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing
DECK ENGAGEMENT	Ogura® G13.5 Electric Clutch	Ogura® G13.5 Electric Clutch	Ogura® G13.5 Electric Clutch	Ogura® G13.5 Electric Clutch	Ogura® G13.5 Electric Clutch	Ogura® G13.5 Electric Clutch	Ogura® G13.5 Electric Clutch
CUTTING WIDTH	52"	52"	60"	60"	60"	72"	72"
CUTTING HEIGHT	1.0"-5.5"	1.0"-5.5"	1.0"-5.5"	1.0"-5.5"	1.0"-5.5"	1.0"-5.5"	1.0"-5.5"
CUTTING POSITIONS	19	19	19	19	19	19	19

### WHEELS

FRONT AXLE	Fixed with greaseable castor fork tubes	Fixed with greaseable castor fork tubes	Fixed with greaseable castor fork tubes	Fixed with greaseable castor fork tubes	Fixed with greaseable castor fork tubes	Fixed with greaseable castor fork tubes	Fixed with greaseable castor fork tubes
FRONT	Smooth 15 x 6-6	Smooth 15 x 6-6	Smooth 15 x 6-6	Smooth 15 x 6-6	Smooth 15 x 6-6	Smooth 15 x 6-6	Smooth 15 x 6-6
REAR	Radial Turf 23x10-12	Radial Turf 23x10-12	Radial Turf 23x10-12	Radial Turf 23x10-12	Radial Turf 23x10-12	Radial Turf 23x10-12	Radial Turf 23x10-12

### FEATURES

SEAT	High Back Comfort w/ Full Air Ride Suspension	High Back Comfort w/ Full Air Ride Suspension	High Back Comfort w/ Full Air Ride Suspension	High Back Comfort w/ Full Air Ride Suspension	High Back Comfort w/ Full Air Ride Suspension	High Back Comfort w/ Full Air Ride Suspension	High Back Comfort w/ Full Air Ride Suspension
HOOD	N/A	N/A	N/A	N/A	N/A	N/A	N/A
FOLDABLE ROPS	3 Positions	3 Positions	3 Positions	3 Positions	3 Positions	3 Positions	3 Positions

### MACHINE

WEIGHT (LBS) W/O FUEL	1317	1317	1400	1400	1360	1433	1360
LENGTH	80"	82"	80"	80"	80"	82"	80"
WIDTH W/O CHUTE	55.5"	55.5"	63"	63"	63"	75"	63"
WIDTH W/ CHUTE	67.75"	67.75"	75.25"	75.25"	75.25"	87.25"	75.25"
HEIGHT W/ ROPS EXT/DOWN	70" / 47.75"	70" / 47.75"	70" / 47.75"	70" / 47.75"	70" / 47.75"	70" / 47.75"	70" / 47.75"

### WARRANTY

UNIT	3 Year Limited Commercial	3 Year Limited Commercial	3 Year Limited Commercial	3 Year Limited Commercial	3 Year Limited Commercial	3 Year Limited Commercial	3 Year Limited Commercial
DECK SHELL & FRAME	Limited Lifetime Deck Shell & Frame	Limited Lifetime Deck Shell & Frame	Limited Lifetime Deck Shell & Frame	Limited Lifetime Deck Shell & Frame	Limited Lifetime Deck Shell & Frame	Limited Lifetime Deck Shell & Frame	Limited Lifetime Deck Shell & Frame
SPINDLES	3 Year Limited	3 Year Limited	3 Year Limited	3 Year Limited	3 Year Limited	3 Year Limited	3 Year Limited

Updated 09/2015

An Ariens Company Brand

© Copyright 2015 Ariens Company. ® Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton, Kubota, Hydro-Gear, Kawasaki, Kohler, Ogura, Parker, Subaru and Warner are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit [www.ariens.com](http://www.ariens.com) for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of product; product may differ.

GRAVELY.com