



# PRO TURN 200



## WELCOME TO HIGHER EXPECTATIONS.

Season after season it delivers superior results. It's really no surprise since it was designed and engineered to take whatever punishment your lawns dish out – can keep you riding comfortably the entire time.

**5YR**  
FIVE YEAR OR 1250 HOUR  
WARRANTY

## 52"

**MODEL - 992268**

27 HP / 852 CC Kawasaki® FX850V Engine

## 60"

**MODEL - 992267**

25 HP / 747 CC Kohler® ZT740 Engine

**MODEL - 992269**

27 HP / 852 CC Kawasaki® FX850V Engine

**MODEL - 992298**

31 HP / 999 CC Kawasaki® FX921V Engine

## 72"

**MODEL - 992270**

31 HP / 999 CC Kawasaki® FX921V Engine

**X-FACTOR® II DECK** Fabricated from top to bottom, it provides industrial-strength peace of mind.

**CONSTANT BELT TENSION SYSTEM (CBT)** Ensures belt tension is constant, blade tip speed is consistent, and cutting results are right on the money.

**FULL SUSPENSION SEAT** 200 series seat with integral suspension for added lateral stability and improved durability, plus added vibration control and a 4-inch seat slide for all-day cruising comfort.

# PRO-TURN® 200



See your professional Gravelly® dealer for complete warranty details.

	252	260	260	260	272
<b>MODEL NUMBER</b>	992268	992267	992269	992298	992270
<b>ENGINE</b>	KAWASAKI® FX850V	KOHLER® ZT740	KAWASAKI® FX850V	KAWASAKI® FX921V0	KAWASAKI® FX921V
	AIR-COOLED, HEAVY-DUTY AIR CLEANER				
<b>HORSEPOWER</b>	27 HP	25 HP	27 HP	31 HP	31 HP
<b>DISPLACEMENT</b>	852 CC	747 CC	852 CC	999 CC	999 CC
<b>DRIVE SYSTEM</b>	HYDRO-GEAR® ZT-5400 TRANSAXLES				
<b>FUEL CAPACITY</b>	13.4 GAL.				
<b>GROUND SPEED</b> (APPROX. Mph) (Forward/Reverse)	13 MPH / 6 MPH				
<b>DECK</b>					
<b>DECK MATERIAL</b>	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT				
<b>DECK CONSTRUCTION</b>	FABRICATED				
<b>NUMBER OF SPINDLES</b>	3				
<b>BLADE TIP SPEED (FPM)</b>	18,000				
<b>SPINDLE HOUSING MATERIAL</b>	FORGED ALUMINUM				
<b>SPINDLE BEARINGS</b>	BALL BEARING				
<b>DECK ENGAGEMENT</b>	OGURA® GT3.5 ELECTRIC CLUTCH				
<b>CUTTING WIDTH</b>	52 IN	60 IN	60 IN	60 IN	72 IN
<b>CUTTING HEIGHTS</b>	1.5 IN. - 5.5 IN.				
<b>CUTTING POSITIONS</b>	17				
<b>WHEELS</b>					
<b>FRONT AXLE</b>	FIXED, GREASEABLE CASTER FORK TUBES				
<b>FRONT</b>	SMOOTH PNEUMATIC 15X6.5-6				
<b>REAR</b>	TURF 23 X 10.5-12	TURF 24 X 12-12	TURF 24 X 12-12	TURF 24 X 12-12	TURF 24 X 12-12
<b>FEATURES</b>					
<b>SEAT</b>	HIGH BACK W/ FULL SUSPENSION & PADDED ARMRESTS				
<b>FOLDABLE ROPS</b>	STANDARD				
<b>MACHINE</b>					
<b>WEIGHT (w/o FUEL)</b>	1315 LBS.	1380 LBS.	1380 LBS.	1395 LBS	1410 LBS
<b>LENGTH</b>	80 IN.	80 IN.	80 IN.	80 IN.	82 IN.
<b>WIDTH (w/o CHUTE)</b>	55.5 IN.	63 IN.	63 IN.	63 IN.	75 IN.
<b>WIDTH (w/ CHUTE)</b>	67.5 IN.	75 IN.	75 IN.	75 IN.	87 IN.
<b>HEIGHT</b> (W/ ROPS EXT/DOWN)	70 IN. / 47.8 IN.				
<b>WARRANTY</b>					
<b>UNIT</b>	5 YEAR / 1250 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS				
<b>DECK SHELL &amp; FRAME</b>	LIMITED LIFETIME				
<b>ATTACHMENTS &amp; ACCESSORIES</b>					
SEAT ISOLATOR KIT, TIRES, STRIPING KIT, OCDB KIT, SEMI-PNEUMATIC FRONT TIRE KIT AND HEADLIGHT KIT, POWERED BAGGER KIT, MULCHING KIT, TRAILER HITCH KIT, SUNSHADE KIT, REAR TWEEL KIT, RADIAL DRIVE CONVERSION KIT, AIR RIDE SEAT KIT, WHEEL COVER KIT, LASEREDGE BLADES, TUNE UP KIT					

