

GRAVELY

PRO-[®]STANCE

STEP UP TO GREATNESS.

The perfect blend of power and performance for environments that demand quick on-and-off versatility. The deck adjusts easily, and the suspension platform absorbs vibration for all-day comfort.

5YR
FIVE YEAR OR 1000 HOUR
WARRANTY



DECK HEIGHT ADJUSTMENT

The dual height-adjustment system was designed with both a traditional hand lever and a foot lever to lift and adjust the deck. It's perfect for smaller operators who may struggle with traditional hand lever lifts.

TRANSMISSION

The ZT-3400 integrated transmission boasts an industry-leading 1.125-inch axle for heavy loads (32" and 36" model uses ZT-3100).

X-FACTOR[®] 3 DECK

The deck has been completely redesigned for better grass dispersion. Its new look is constructed from 7-gauge steel to deliver years of solid performance.

32"

MODEL - 994157

18.5 HP / Kawasaki[®] FS600 V-TWIN

36"

MODEL - 994149

18.5 HP / Kawasaki[®] FS600 V-TWIN

48"

MODEL - 994161

23.5 HP / Kawasaki[®] FX730 V-TWIN

52"

MODEL - 994162

23.5 HP / Kawasaki[®] FX730 V-TWIN

MODEL - 994163

26 HP / Kawasaki[®] FT730 EFI

60"

MODEL - 994164

23.5 HP / Kawasaki[®] FX730 V-TWIN

MODEL - 994165

26 HP / Kawasaki[®] FT730 EFI

★ MADE IN THE UNITED STATES ★
★ WITH GLOBALLY SOURCED PARTS ★

	32	36	48	52	52	60	60
MODEL NUMBER	994157	994149	994161	994162	994163	994164	994165
ENGINE	KAWASAKI® FS 600V	KAWASAKI® FS 600V	KAWASAKI® FX 730V	KAWASAKI® FX 730V	KAWASAKI® FT 730 EFI	KAWASAKI® FX 730V	KAWASAKI® FT730EFI
HORSEPOWER	18.5		23.5 HP	23.5 HP	26 HP	23.5 HP	26 HP
DISPLACEMENT	603 CC		726 CC	726 CC	726 CC	726 CC	726 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-3100 TRANSAXLE		HYDRO-GEAR® ZT-3400 TRANSAXLE				
FUEL CAPACITY	6 GAL		9 GAL				
GROUND SPEED (APPROX) (Forward/Reverse)	8 MPH / 3 MPH		9 MPH / 4 MPH				
STARTER	ELECTRIC						
DECK							
DECK MATERIAL	7 GA.						
DECK CONSTRUCTION	FABRICATED X-FACTOR® 3 DECK						
NUMBER OF SPINDLES	2		3				
BLADE TIP SPEED (FPM)	18,220		18,000				
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM						
SPINDLE BEARINGS	DOUBLE LIP SEAL BALL BEARINGS						
DECK ENGAGEMENT	WARNER® ELECTRIC CLUTCH						
DECK LIFT SYSTEM	FOOT PEDAL AND LEVER LIFT SYSTEM						
CUTTING WIDTH	32 IN	36 IN	48 IN	52 IN	52 IN	60 IN	60 IN
CUTTING HEIGHTS	1.0 IN - 5.0 IN						
CUTTING POSITIONS	15						
WHEELS							
FRONT	11 X 4.00-5 PNEUMATIC		13 X 6.50-6 PNEUMATIC				
REAR	18 X 6.50 - 8	18 X 8.50 - 8	20 X 10.50 - 8				
MACHINE							
WEIGHT	762 LBS	776 LBS	875 LBS	912 LBS	912 LBS	940 LBS	940 LBS
LENGTH	59.5 IN	59.5 IN	60.63 IN	60.63 IN	60.63 IN	62 IN	62 IN
WIDTH (w/o CHUTE)	33.5 IN	36.5 IN	50 IN	55.5 IN	55.5 IN	63 IN	63 IN
WIDTH (w/ CHUTE)	49 IN	49 IN	62.25 IN	67.75 IN	67.75 IN	75.25 IN	75.25 IN
HEIGHT	48 IN						
WARRANTY							
UNIT	5 YEAR / 1000 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS - SEE YOUR PROFESSIONAL GRAVELLY® DEALER FOR COMPLETE WARRANTY DETAILS						
DECK SHELL & FRAME	LIMITED LIFETIME						

ATTACHMENTS & ACCESSORIES

MULCHING KIT
OCDB KIT
HEADLIGHT KIT
TRIMMER MOUNT KIT
PACK BLOWER MOUNT KIT
BUCKET MOUNT KIT
REAR TWEEL KIT
LASEREDGE BLADES
TUNE UP KIT